

Stucco Italiano



STUCCO AQUAGUARD BRUSH ON

DESCRIPTION

STUCCO AQUAGUARD BRUSH-ON creates a unique, textured and slightly rough finish suitable for interior as well as exterior walls.

Applied with a block-brush onto concrete, cement plaster, fair face brickwork and many other types of wall surfaces, it creates a mottled finish that matures over time.

PURPOSE

STUCCO AQUAGUARD BRUSH ON provides a tough, waterproofing durable cement-based coating for interior as well as exterior walls.

STUCCO AQUAGUARD BRUSH-ON can withstand negative as well as positive water pressure.

APPLICATION

Necessities

1 bag of 20kg STUCCO AQUAGUARD BRUSH-ON; 2.9lt STUCCO AQUAGUARD LIQUID; 5lt water; 40lt mixing bowl; measuring jug; gloves; block-brush; masking tape; drop sheets.

Preparation

Surface must be clean and free from any dust, saline deposits, greasiness or any materials that can prevent binding.

Saline deposits and greasiness can be washed off with washing soda.

Never apply Stucco to Cretestone or gypsum based wall renders.

In case of a smooth, glossy, textured paint such as an oil based paint, sand the surfaces to obtain a bonding surface using a fine sanding paper, remove any remaining dust and loose particles and paint.

In the case of a wall being very uneven, it is recommended to first apply a pre-screed layer of STUCCO WALL SKIM to smooth out any unevenness, let it cure and then apply one layer of STUCCO AQUAGUARD BRUSH ON.

Mixing Instructions

Pour 5lt water and 2,9lt of STUCCO AQUAGUARD LIQUID into a 40lt mixing bowl and stir.

Gradually add the STUCCO AQUAGUARD BRUSH ON powder, while continuously mixing with hands (covered with gloves), to prevent lumps from being formed, until the full amount of 20kg STUCCO AQUAGUARD BRUSH ON powder is thoroughly mixed.

Application

Cover windows, doors and light fittings with masking tape and paper and put drop sheets on floor.

Use a block-brush and paint onto the wall one layer of STUCCO AQUAGUARD BRUSH ON, making strokes in vertical direction only. Finish the wall from top to bottom with block-brush in one single stroke to avoid joints.

Other paint techniques can be applied, but that remains the responsibility of the applicator.

Let the first coat dry for a minimum of 6 hours before applying the second coat in similar fashion.

On very hot, windy days, pre-wet exterior walls when applying the first coat only to saturate the wall, painting onto a damp surface.

Stucco Italiano



SEALERS
<p>Leave the walls to dry for about 1 day before applying STUCCO EXTERIOR SEALER or STUCCO INTERIOR WALL SEALER.</p> <p>Interior walls: Apply a single layer of STUCCO INTERIOR WALL SEALER with a paint brush or roller.</p> <p>Exterior walls: Apply a single layer of STUCCO COLOUR FASTENER and allow to dry overnight. Then apply a single layer of STUCCO EXTERIOR SEALER with a spray-can or a roller.</p>
TECHNICAL DATA
<p>Type: Cement based Drying time: 6 hours @ 20°C Shelf life: 6 months Coverage: ±12 m² per 20KG bag (two coats) Packaging: 20kg powder in paper bags 2.9lt liquid in plastic bottles Storage: Store in a cool dry place</p>
WARNING
<p>Do not ingest. Keep away from children and pets. Do not empty into drains.</p>
PRECAUTIONS
<p>Wear rubber gloves. In the event of contact with eyes or skin, rinse thoroughly with cold water. If irritation or discomfort occurs, seek medical advice.</p>
MANUFACTURED BY
<p>Stucco Italiano 25 Industria Rd Brackenfell Tel: 021-982 0006 Fax: 021-982 3796 E-mail: info@stuccoitaliano.co.za www.stuccoitaliano.co.za</p>