

Stucco Italiano



STUCCO FLOOR FIXING KIT

DESCRIPTION

STUCCO FLOOR FIXING KIT is a polymer-modified cementitious product, consisting of a 20kg bag of a cement mortar powder mix with excellent levelling properties.

PURPOSE

The purpose of the STUCCO FLOOR FIXING KIT is to level and smooth out uneven floors and to fill up floor cavities yielding a final strength of about 35 MPa. STUCCO FLOOR FIXING KIT can also be used over tiles in which case it is mixed with 4L of FLOORMIX.

The product can be applied from 3mm up to 10mm thick and has excellent selflevelling properties.

Should a thickness of more than 6mm be required, a second layer of STUCCO FLOOR FIXING KIT can be applied to obtain the required thickness.

APPLICATION

Preparation

Make sure the floor is dust, dirt and oil free.

Degrease the floor if necessary using a floor degreaser.

Make sure the floor is dry, remove all loose particles, and grind the floor to remove any protrusions and to obtain a sound bonding surface.

When working over tiles, first seal off the grout lines using STUCCO FLOOR SEALER and allow to dry, to prevent uneven absorption of the product.

When onto a very smooth or polished cementitious or concrete surface, apply POWERSCREED LIQUID as a primer at a rate of 12m²/L to 16m²/L and while the primer is still tacky, apply the STUCCO FLOOR FIXING KIT.

Mixing

Decant 3L of water into a suitable container and gradually add the powder, while continuously mixing. The product will have a runny consistency.

Continue mixing the product during application, to prevent the product from settling.

Application

Pour the contents of the mixing bowl onto the floor in longitudinal beads and spread it with a steel trowel to a thickness of 2–3mm, filling all indentations and smooth the floor out.

Should depressions be more than 30mm, 6mm stone may be added to the mixture to a ratio of about 40% of stone by volume of the total mixture, which can be applied in one single layer.

TECHNICAL DATA

Type: Polymer modified cement
Drying time: 24 hours
Coverage: 4 – 5m² per bag (one coat, 2-3mm)

Stucco Italiano



PACKAGING AND STORAGE DATA

Shelf life: 6 months
Packaging: 20kg powder in paper bags
Storage: Store in a cool, dry place

WARNING

Do not ingest. Keep away from children and pets. Do not empty into drains.

PRECAUTIONS

Wear rubber gloves. In the event of contact with eyes or skin, rinse thoroughly with cold water. If irritation or discomfort occurs, seek medical advice.

MANUFACTURED BY

Stucco Italiano
25 Industria Rd
Brackenfell
Tel: 021- 982 0006
Fax: 021-982 3796
E-mail: info@stuccoitaliano.co.za
www.stuccoitaliano.co.za