

Stucco Italiano



STUCCO SKIMMING COMPOUND

DESCRIPTION

STUCCO SKIMMING COMPOUND is a specially formulated thin plaster for skimming uneven and damaged walls.

PURPOSE

STUCCO SKIMMING COMPOUND is applied to walls where limited space is left for plasterwork and for skimming uneven and damaged walls. It creates a smooth, solid finish and sound working surface for both exterior as well as interior wall surfaces. It can also be applied to smooth cement surfaces.

APPLICATION

Preparation

Walls must be clean and all cracks need to be repaired.

Remove any loose particles and dust.

In very hot windy conditions, pre-wet the wall to avoid rapid evaporation and drying of the product and liquid.

Mixing

STUCCO SKIMMING COMPOUND is mixed with water to obtain a soft paste consistency.

Pour 6lt to 7lt of water into a suitable container and gradually add the 20kg STUCCO SKIMMING COMPOUND powder while stirring.

Mix until a soft paste-like consistency is obtained.

Application

Apply with a steel trowel and finish it off smoothly. Allow 24 hours for the STUCCO SKIMMING COMPOUND to dry.

STUCCO SKIMMING COMPOUND cannot be applied directly onto Cretestone or Rhinolite surfaces. Remove any Cretestone or Rhinolite before applying STUCCO SKIMMING COMPOUND.

If applied exteriorly, mix 20kg STUCCO WALL SKIM with 4.5L STUCCO AQUAGUARD LIQUID

TECHNICAL DATA

Type: Cement based
Drying time: 24 hours @ 20°C
Shelf life: 6 months
Packaging: 20kg in paper bags
Storage: In a cool dry place
Coverage: Depending on profile of the wall, but one bag can cover up to 15m² (one coat)
Water addition: 6 – 7 litres

WARNING

Do not ingest. Keep away from children and pets. Do not empty into drains.

PRECAUTIONS

Wear rubber gloves. In the event of contact with eyes or skin, rinse thoroughly with cold water. If irritation occurs, seek medical advice.

Stucco Italiano



MANUFACTURED BY

Stucco Italiano
25 Industria Rd
Brackenfell
Tel: 021- 982 0006
Fax: 021-982 3796
E-mail: info@stuccoitaliano.co.za
www.stuccoitaliano.co.za